



Manual for Computerboard

ADL120

Version: 0.3
Date: 02.04.2019

1 Documentation issue status	7
2 Notes on the documentation	8
3 Safety instructions	9
4 Overview.....	10
4.1 Properties	10
4.2 List of features	11
4.3 Specifications and documents	12
5 Detailed description	13
5.1 Power supply	13
5.2 CPU	13
5.3 Memory	13
5.4 M.2.....	13
6 External connections	14
6.1 Note on the use of cables	14
6.2 Connector Map	15
6.3 Interface list	16
6.4 Front panel: Power supply (X101).....	17
6.5 Front panel: LAN1-4 (X102-X105).....	18
6.6 Front panel: USB 3.0 A-D (X106 - X109)	19
6.7 Front panel: DisplayPort (X110, X110).....	20
7 Internal connections.....	21
7.1 Internal: M.2.....	21
7.2 Internal: BASeCon140 (Q170 only).....	24
7.3 Internal: FAN	28
7.4 Internal: Battery	29
8 LEDs.....	30
8.1 LED: Power controller.....	30
8.2 LED: SATA	31
8.3 LED: TwinCAT	32
8.4 LED: UPS-OCT.....	33
9 BIOS.....	34
9.1 Main.....	34
9.2 Advanced Menu.....	35
9.3 Platform Misc Configuration	36
9.4 CPU Configuration.....	37
9.5 CPU Power Management Control	38
9.6 Intel Ethernet Connection	38
9.7 NIC Configuration	39
9.8 Driver Health.....	39
9.9 Intel Gigabit	39
9.10 Trusted Computing	40
9.11 Hardware Monitor	40

9.12	PCI Subsystem Settings	41
9.13	PCI Hot-Plug Settings.....	41
9.14	Network Stack Configuration	42
9.15	Power Controller Options	43
9.16	CSM Configuration	44
9.17	NVMe Configuration	45
9.18	USB Configuration.....	45
9.19	SATA und RST Configuration.....	46
9.20	Software Feature Mask Configuration	47
9.21	AMT Configuration.....	48
9.22	CIRA Configuration.....	48
9.23	ASF Configuration	49
9.24	Secure Erase Configuration	49
9.25	OEM Flags Settings.....	50
9.26	MEBx Resolution Settings	51
9.27	Chipset	51
9.28	System Agent (SA) Configuration.....	52
9.29	Graphics Configuration	53
9.30	External Gfx Card Primary Display Configuration	54
9.31	LCD Control.....	54
9.32	PCH-IO Configuration.....	55
9.33	PCI Express Configuration	56
9.34	PCI Express Gen3 Eq Lanes.....	56
9.35	PCI Express Root Port X	57
9.36	Extra Options	58
9.37	USB Configuration	58
9.38	HD Audio Configuration	59
9.39	Security	59
9.40	Secure Boot	60
9.41	Key Management	60
9.42	Boot	61
9.43	Fixed Boot Order Parameters.....	62
9.44	Save & Exit	62
10	Mechanical drawings	63
10.1	PCB: Holes	63
10.2	PCB: Pin 1 distances	64
10.3	PCB: Dimensions	65
11	Technical data.....	66
11.1	Electrical data	66
11.2	Environmental conditions	66
11.3	Technical specifications.....	67
12	Support	68
12.1	ADL Support	68

13 Appendix I: Post Codes	69
14 Appendix II: Resources.....	70
14.1 Interrupt	70
14.2 PCI Devices.....	71
14.3 SMB-Devices.....	72

Preliminary

Preliminary

1 Documentation issue status

Version	Modifications
0.1	Preliminary version
0.2	Preliminary version, change of the fan plug from 3 to 4-pin, OCT UPS, OCT LED inserted, graphics for LEDs changed, mechanical drawings updated
0.3	Interface assignment added

Preliminary

2 Notes on the documentation

This description is only intended for the use of trained specialists in control and automation engineering who are familiar with the applicable national standards.

It is essential that the documentation and the following notes and explanations are followed when installing and commissioning the components.

It is the duty of the technical personnel to use the documentation published at the respective time of each installation and commissioning.

The responsible staff must ensure that the application or use of the products described satisfy all the requirements for safety, including all the relevant laws, regulations, guidelines and standards.

Disclaimer

The documentation has been prepared with care. The products described are, however, constantly under development.

We reserve the right to revise and change the documentation at any time and without prior announcement. No claims for the modification of products that have already been supplied may be made on the basis of the data, diagrams and descriptions in this documentation.

Warranty

This product is warranted to be free of defects in workmanship and material. ADL Embedded Solutions' sole obligation under this warranty is to provide replacement parts or repair services at no charge, except shipping cost. Such defects which appear within 12 months of original shipment of ADL Embedded Solutions will be covered, provided a written claim for service under warranty is received by ADL Embedded Solutions no less than 30 days prior to the end of the warranty period or within 30 days of discovery of the defect – whichever comes first. Warranty coverage is contingent upon proper handling and operation of the product. Improper use such as unauthorized modifications or repair, operation outside of specified ratings, or physical damage may void any service claims under warranty.

Return Authorization

All equipment returned to ADL Embedded Solutions for evaluation, repair, credit return, modification, or any other reason must be accompanied by a Return Material Authorization (RMA) number. ADL Embedded Solutions requires a completed RMA request form to be submitted in order to issue an RMA number. The form can be found under the Support section at our website: www.adl-usa.com or www.adl-europe.com. Submit the completed form to support@adl-usa.com or fax to +1 858-490-0599 for the USA office, or to rma@adl-europe.com or fax to +49 (0) 271 250 810 20 to request an RMA from the European office in Germany. Following a review of the information provided, ADL Embedded Solutions will issue an RMA number.

3 Safety instructions

Safety regulations

Please note the following safety instructions and explanations!

Product-specific safety instructions can be found on following pages or in the areas mounting, wiring, commissioning etc.

Exclusion of liability

All the components are supplied in particular hardware and software configurations appropriate for the application. Modifications to hardware or software configurations other than those described in the documentation are not permitted, and nullify the liability of ADL Embedded Solutions.

Personnel qualification

This description is only intended for trained specialists in control, automation and drive engineering who are familiar with the applicable national standards.

Description of symbols

In this documentation the following symbols are used with an accompanying safety instruction or note. The safety instructions must be read carefully and followed without fail!

DANGER

Serious risk of injury!

Failure to follow the safety instructions associated with this symbol directly endangers the life and health of persons.

WARNING

Risk of injury!

Failure to follow the safety instructions associated with this symbol endangers the life and health of persons.

CAUTION

Personal injuries!

Failure to follow the safety instructions associated with this symbol can lead to injuries to persons.

NOTE

Damage to the environment or devices

Failure to follow the instructions associated with this symbol can lead to damage to the environment or equipment.

Tip or pointer

This symbol indicates information that contributes to better understanding.

4 Overview

4.1 Properties

The ADL120 is designed as a high-performance compact board based on Intel®'s Skylake and Kabylake processors. The latest energy-saving DDR4 technology enables memory extension of up to 32 GB via SO-DIMM260.

As standard interfaces two DisplayPort connections, four Gigabit LAN connections and four USB 3.0 interfaces are available on the front panel. *The two DisplayPorts++ enable the connection of an HDMI adapter for an HDMI signal. The connection of an HDMI display with adapter is possible.*

Two variants are available, variant 1 being equipped with a Q170 chipset and variant 2 with an H110 chipset.

Internally both variants of the ADL120 have two M.2 (B) sockets (2280), while variant 1 additionally has a BBaseCon140 connector. Various signals, which are listed in the respective chapter, are led out via the internal plug connector depending on the chipset in use.

Power is supplied via a 4-pin connector on the front panel. Input voltage is isolated 24 V.




Fig. 1: Block diagram_ADL120

4.2 List of features

ADL120	120 x 120 board
CPU	Intel® Core™ i3 / Core™ i5 / Core™ i7 Intel® Pentium® Intel® Celeron®
Memory	2x SO-DIMM260 1.2V DDR4-2133 Maximum memory extension 32 GB
I/O on front panel	2x DisplayPort++ (connection of an HDMI adapter for an HDMI signal is possible.) 4x GB LAN 4x USB 3.0
Internal I/O	2x M.2 (B) sockets, signals dependent on chipset <u>Internal: M.2 [▶ 21]</u> With Q170 only: 1x BAseCon140 <u>Internal: BAseCon140 (Q170 only) [▶ 24]</u>
Graphic resolution	DisplayPort: 4096x2304@60 Hz HDMI1.4: 2560x1600@60 Hz; 4096x2160@24 Hz DVI: 1920x1200@60 Hz
RTC	Exchangeable, horizontal on-board battery Optional: horizontal battery on expansion card
BIOS	AMI® Aptio V
Power supply	24 V
Format	120 x 120 mm



Availability of the processors

The list of features lists all the processors that can be ordered. Their actual availability depends on the manufacturer.

4.3 Specifications and documents

The following documents, specifications or webpages were used for the preparation of this manual or as further technical documentation respectively.

- **PCI specification**
- Version 2.3 or 3.0
- www.pcisig.com
- **PCI Express® Base Specification**
- Version 2.0
- www.pcisig.com
- **ACPI specification**
- Version 3.0
- www.acpi.info
- **ATA/ATAPI specification**
- Version 7 Rev. 1
- www.t13.org
- **USB specifications**
- www.usb.org
- **SM-Bus specification**
- Version 2.0
- www.smbus.org
- **Intel® chip descriptions**
- Intel® Atom™ Processor E3800 Product Family datasheet
- www.intel.com
- **Intel® chip description**
- i210 datasheet
- www.intel.com
- **SMSC® chip description**
- SCH3114 datasheet (NDA required)
- www.smsc.com
- **American Megatrends®**
- Aptio™ Text Setup Environment (TSE) User Manual
- www.ami.com
- **American Megatrends®**
- Aptio™ 4.x Status Codes
- www.ami.com

5 Detailed description

5.1 Power supply

The board is supplied with an isolated input voltage of nominally 24 V, which in reality may lie between 20 V and 30 V. In normal operation the DC/DC power rail is supplied with this voltage. A UPS can also be implemented via an OCT signal (OCT = One Cable Technology).



UPS-OCT

The UPS-OCT can only be implemented with the Beckhoff CU81XX-xxxx UPS.

5.2 CPU

The processors employed are Intel® processors of the 6th (Skylake) and 7th (KabyLake) generation. Processors of both generations are characterized by a very low power consumption and offer contemporary performance with clock rates of currently up to 3.9 GHz.

5.3 Memory

SO-DIMM260 memory modules (DDR4-2133) commonly used in notebooks are used on the ADL120 board. For technical and mechanical reasons it is possible that certain memory modules cannot be used. Ask your distributor about the recommended memory modules.

With the currently available SO-DIMM260 modules a memory extension up to 32 GB is possible depending on the product variant. When equipping both memory sockets, care must be taken that identical memory modules are used.

5.4 M.2

Expansion cards that fulfill the M.2 specification are characterized by an extremely small format and – depending on the card type – flexible dimensions.

M.2 cards can easily and simply be inserted by plugging them into the slot and fixing them with a screw.

The M.2 socket of the ADL120 supports Key B. Different signals are supported depending on the chipset in use. The table in chapter M.2 lists all the interfaces supported, depending on the chipset in use.



Driver compatibility

For optimum driver compatibility we recommend the use of a Microsoft® Windows 10 operating system.

6 External connections

6.1 Note on the use of cables



Requirement for the cabling!

The cables used must meet certain requirements for most interfaces. For example, twisted and shielded cables are necessary for a reliable USB 2.0 connection. Limitations in the maximum cable length are also no rarity. All of these interface-specific requirements are to be taken from the respective specifications and observed accordingly.

6.2 Connector Map

The plug connections on the component side of the ADL120 board are summarized in the illustration below. The function of the respective connector can be taken from the table below the illustration, as can the page of the manual on which further information about this connection can be read.




Fig. 2: Connector Map

6.3 Interface list

Number	Function (Designation)	Page
P1500	Vin (X101)	Front panel: Power supply (X101) [▶ 17]
P1100	LAN 1 (X102)	Front panel: LAN1-4 (X102-X105) [▶ 18]
P1100	LAN 2 (X103)	Front panel: LAN1-4 (X102-X105) [▶ 18]
P1101	LAN 3 (X104)	Front panel: LAN1-4 (X102-X105) [▶ 18]
P1101	LAN 4 (X105)	Front panel: LAN1-4 (X102-X105) [▶ 18]
P1102	USB3.0 (X106)	Front panel: USB 3.0 A-D (X106 - X109) [▶ 19]
P1102	USB3.0 (X107)	Front panel: USB 3.0 A-D (X106 - X109) [▶ 19]
P1102	USB3.0 (X108)	Front panel: USB 3.0 A-D (X106 - X109) [▶ 19]
P1102	USB3.0 (X109)	Front panel: USB 3.0 A-D (X106 - X109) [▶ 19]
P1103	DisplayPort (X110, X111)	Front panel: DisplayPort (X110, X110) [▶ 20]
P1200/1*	M.2, Key B	Internal: M.2 [▶ 21]
P1203*	BAseCon140	Internal: BAseCon140 (Q170 only) [▶ 24]
P500/501	FAN	Internal: Battery [▶ 29]
BT1200*	Battery	Internal: FAN [▶ 28]

*not depicted (see bottom of board)



The numbers in brackets correspond to the inscription of the external interfaces on the front housing of the industrial pc.

6.4 Front panel: Power supply (X101)

The connection to the power supply is implemented as a 2x2-pin housing plug (Phoenix Contact P20THR-1818504). The main supply voltage (24 V) for the module is on PIN 3. This can also be implemented as UPS-OCT (One Cable Technology), i.e. the signal for the UPS is also transmitted to the board via this cable.




Fig. 3: ADL120 Vin



90° plug

As the plug is a 90° plug, the plug symbol in the illustration is oriented to what you see when you look at the board from the side (instead of from above).

Pin assignment of the power plug:

Description	Signal	Pin	Signal	Description
PC Start: Input for starting and shutting down the PC. Low (0 V or open contact): PC starts. High (>3 V): PC shuts down.	PC_START	1	3	Vin 24 V supply voltage UPS OCT is supported
PC Status: Output of the PC status. The voltage corresponds to the positive supply voltage and can be loaded with 1 A. Low (0 V): PC is off. High (Vin): PC is on.	PC_ACTIVE	2	4	GND Ground

6.5 Front panel: LAN1-4 (X102-X105)

The board has four Gigabit-LAN connections, which are implemented with two standard connectors, each with two connections. Network components compatible with 10BaseT, 100BaseT and 1000BaseT can be connected to all of them. The required speed is selected automatically. Auto-Cross and Auto-Negotiate are available as well as PXE, RPL and WOL functionality. Intel® i219 (PHY) is the controller for LAN1, while Intel® i210 (MAC/PHY) is used as the controller for LAN 2 to 4.



Real-time applications



The Ethernet port connected via PCIe is usually suitable for cycle times ≤ 1 ms and for distributed clock applications with EtherCAT.

The Ethernet port integrated in the chipset is usually suitable for real-time Ethernet applications with cycle times > 1 ms (without distributed clocks).




Fig. 4: ADL120 LAN



90° plug

As the plug is a 90° plug, the plug symbol in the illustration is oriented to what you see when you look at the board from the side (instead of from above).

Pin assignment of LAN connector:

Pin	Name	Description
1	LAN-0	LAN line 0 plus
2	LAN-0#	LAN line 0 minus
3	LAN-1	LAN line 1 plus
4	LAN-2	LAN line 2 plus
5	LAN-2#	LAN line 2 minus
6	LAN-1#	LAN line 1 minus
7	LAN-3	LAN line 3 plus
8	LAN-3#	LAN line 3 minus

The LEDs of the LAN interfaces indicate the activity and speed of the data transmission:

Mbit/s	Flashing during data transmission	Steadily lit
1000	Green	Green
100	Green	Orange
10	Green	None

6.6 Front panel: USB 3.0 A-D (X106 - X109)

The ADL120 provides four USB 3.0 ports, which are implemented as combination connectors with 4 connectors.

The USB channels support the USB 3.0 specification. All necessary settings for USB can be made in the BIOS. Note that the "USB mouse and keyboard" function in the BIOS setup is only required if the operating system does not offer USB support. This function should not be selected for settings in the setup and for booting Windows with a USB mouse and keyboard connected, because this would lead to considerable performance limitations.

The individual USB interfaces can supply a current of up to 900 mA and are electronically protected.



Switch-off of the USB ports by overcurrent protection

USB ports A and B and USB ports C and D are each protected by a common overcurrent detection. In the event of overcurrent occurring on one of the ports, therefore, both commonly protected USB ports will be switched off.




Fig. 5: ADL120 USB 3.0



90° plug

As the plug is a 90° plug, the plug symbol in the illustration is oriented to what you see when you look at the board from the side (instead of from above).

Pin assignment of USB 3.0 connector:

Pin	Signal	Description
1	VCC	5 V supply voltage
2	D-	Data minus (USB 2.0)
3	D+	Data plus (USB 2.0)
4	GND	Ground
5	Rx-	Receive line minus
6	RX+	Receive line plus
7	GND	Ground
8	TX-	Transmit line minus
9	TX+	Transmit line plus

6.7 Front panel: DisplayPort (X110, X111)

For devices with a DisplayPort connection a corresponding standard connector (Foxconn 3VD11203-DPA1-4H) with two DisplayPort connections is available.

The interface additionally provides HDMI/DVI signals that can be used with aid of an adapter. Please consult your distributor with regard to a suitable adapter.




Fig. 6: ADL120 Display Port

 **90° plug**

 As the plug is a 90° plug, the plug symbol in the illustration is oriented to what you see when you look at the board from the side (instead of from above).

Pin assignment of DisplayPort plug:

Description	Signal	Pin		Signal	Description
Line 0 plus	L0	1	2	GND	Ground
Line 0 minus	L#0	3	4	L1	Line 1 plus
Ground	GND	5	6	L#1	Line 1 minus
Line 2 plus	L2	7	8	GND	Ground
Line 2 minus	L#2	9	10	L3	Line 3 plus
Ground	GND	11	12	L#3	Line 3 minus
HDMI	HDMI#	13	14	GND	Ground
Auxiliary plus	AUX	15	16	GND	Ground
Auxiliary minus	AUX#	17	18	HPD	Hot Plug Detect
Ground	GND	19	20	3.3 V	3.3 V supply voltage

 **Switching to HDMI**

DisplayPort signals are led out via the interface by default. With the use of a level shifter cable the board switches according to the DisplayPort specification 1.1 automatically to HDMI signals.

7 Internal connections

7.1 Internal: M.2

The ADL120 is equipped with two M.2 sockets, into each of which an M.2-2280 card (Key B) is inserted. Various signals are led out via the socket, depending on the chipset (see table).

Q170	H110
2x USB 3.0 (1x per socket)	2x USB 2.0 (1x per socket)
2x SATA Gen 3 (1x per socket) or	2x SATA Gen 3 (1x per socket)
2x PCIe x1 Gen 3 (1x per socket) or	
1x PCIe x1 and 1x SATA Gen 3	

Adapter cards with standard plug connectors are available as accessories. Please contact your distributor for this.




Fig. 7: ADL120 M.2

Pin assignment of M.2 connector:

Description	Signal	Pin		Signal	Description
Configuration pin	CONFIG_3	1	2	3.3 V1	Standby supply voltage S 3.3 V
Ground	GND	3	4	3.3 V2	Standby supply voltage S 3.3 V
Ground	GND	5	6	FCPWROFF#	Full Card Power OFF active low
USB Channel 2 Data +	USB D+	7	8	WDISABLE#	(not led out)
USB Channel 2 Data -	USB D-	9	10	GPIO9 DAS DDS LED1	(not led out)

Ground	GND	11	12	Connector Key	
Connector Key		13	14		
		15	16		
		17	18		
		19	20	GPIO5	(not led out)
Configuration pin (not led out)	Config 0 GPIO11	21 23	22 24	GPIO6 GPIO7	(not led out)
(not led out)	DPR	25	26	GPIO10	(not led out)
Ground	GND	27	28	GPIO8	(not led out)
USB 3.0 Channel 5 SuperSpeed Receive -	PER1# USB3-5 SSRX# SSICRX#	29	30	UIM RST	(not led out)
USB 3.0 Channel 5 SuperSpeed Receive	PER1 USB3-5 SSRX SSICRX	31	32	UIM CLK	(not led out)
Ground	GND	33	34	UIM DATA	(not led out)
USB 3.0 Channel 5 SuperSpeed Transmit -	PET1# USB3-5 SSTX# SSICTX#	35	36	UIM PWR	(not led out)
USB 3.0 Channel 5 SuperSpeed Transmit +	PET1 USB3-5 SSTX SSICTX	37	38	DEVSLP	DeviceSleep
Ground	GND	39	40	GPIO0	(not led out)
PCIe Lane 1 Receive +	PER0# SATAB	41	42	GPIO1	(not led out)
PCIe Lane 1 Receive -	PER0 SATAB#	43	44	GPIO2	(not led out)
Ground	GND	45	46	GPIO3	(not led out)
PCIe Lane 1 Transmit -	PET0# SATAA#	47	48	GPIO4	(not led out)
PCIe Lane 1 Transmit +	PET0 SATAA	49	50	PRST#	PCIe Reset active low
Ground	GND	51	52	CLKREQ#	PCIe Clock Enable active low
PCIe Lane 1 Reference Clock -	REFCLK#	53	54	PEWAKE#	Link Reactivation active low
PCIe Lane 1 Reference Clock -	REFCLK	55	56	N/C	(not led out)
Ground	GND	57	58	N/C	(not led out)
(not led out)	ANTCTL0	59	60	COEX3	(not led out)
(not led out)	ANTCTL1	61	62	COEX2	(not led out)
(not led out)	ANTCTL2	63	64	COEX1	(not led out)
(not led out)	ANTCTL3	65	66	SIM DETECT	(not led out)
Power good	RESET#	67	68	SUSCLK	System clock
Configuration pin	CFG1	69	70	3.3 V	Standby supply voltage S 3.3 V
Ground	GND	71	72	3.3 V	Standby supply voltage S 3.3 V

Ground	GND	73	74	3.3 V	Standby supply voltage S 3.3 V
Configuration pin	CFG2	75			

Preliminary

7.2 Internal: BAsenCon140 (Q170 only)

In conjunction with the Q170 chipset, the BAsenCon140 connector enables the flexible extension of the IO functions of the ADL120. It provides up to eight PCIe lanes, of which a maximum of four can be multiplexed with SATA 2.0 (3G) and a maximum of four with PCIe lines, as well as a maximum of four PCIe lines with a maximum of four USB 3.0 lines (see table). In addition, DisplayPort, SSIC, SMBus and 1Wire signals are led out via the BAsenCon connector. The expansion board takes care of the configuration of the IO functions. A PIC on the expansion card contains the configuration data that are communicated to the board upon connection, thus enabling an uncomplicated and self-configuring extension to the IO options.

With Q170 only	
Max. 4x SATA Gen 3 / max. 4x PCIe x1 Gen 3 (multiplexed)	Total: 8x PCIe x1 (configurable – see left)
Max. 4x USB 3.0 / max. 4x PCIe x1 Gen 3 (multiplexed)	
1x DisplayPort 1.4 / HDMI 2.0	



Observe the current limits!

In order to avoid damaging the device, it is essential to observe the following current limits:

A maximum load of 2.8 A per pin must not be exceeded. On account of the different current consumptions of the usable processors the actual current consumption may be lower. The respective maximum values can be obtained from your distributor on enquiry.

Irrespective of the CPU in use, a maximum total load of 100 W must not be exceeded.




Fig. 8: ADL120 BAsenCon

Pin assignment of BAsenCon140 connector:

Description	Signal	Pin	Signal	Description
S UPS output	S UPS OUT1	1	2	S UPS IN1
S UPS output	S UPS OUT2	3	4	S UPS IN2
VCC	5 V1	5	6	GND
VCC	5 V2	7	8	GND
Ground	GND	9	10	3.3 V1
Ground	GND	11	12	3.3 V2
S VCC	S 5 V	13	14	Standby supply voltage 3.3 V
Ground	GND	15	16	Ground

PCIe Lane 1 Transmit +	PE1 TX/ SATA4 TX	17	18	SATA4 RX/ PE1 RX	PCIe Lane 1 Receive +
PCIe Lane 1 Transmit -	PE1 TX#/ SATA4 TX#	19	20	SATA4 RX #/ PE1 RX#	PCIe Lane 1 Receive -
Ground	GND	21	22	GND	Ground
PCIe Clock Lane 1 +	PECLK1	23	24	PECLK2	PCIe Clock Lane 2 +
PCIe Clock Lane 1 -	PECLK1#	25	26	PECLK2#	PCIe Clock Lane 2 -
Ground	GND	27	28	GND	Ground
PCI Lane 2 Transmit +	PE2 TX/ SATA3 TX	29	30	SATA3 RX/ PE2 RX	PCIe Lane 2 Receive
PCI Lane 2 Transmit -	PE2 TX#/ SATA3 TX#	31	32	SATA3 RX #/ PE2 RX#	PCIe Lane 2 Receive -
Ground	GND	33	34	GND	Ground
PCIe Lane 3 Transmit +	PE3-TX/ SATA2-TX	35	36	SATA2 RX/ PE3 RX	PCIe Lane 3 Receive +
PCIe Lane 3 Transmit -	PE3-TX#/ SATA2-TX#	37	38	SATA2 RX #/ PE3 RX#	PCIe Lane 3 Receive -
Ground	GND	39	40	GND	Ground
PCIe Lane 3 Clock +	PECLK3	41	42	PECLK4	PCIe Clock 4 +
PCIe Lane 3 Clock 3 -	PECLK3#	43	44	PECLK4#	PCIe Clock 4 -
Ground	GND	45	46	GND	Ground
SATA Lane 2 Transmit +	PE4-TX/ SATA1-TX	47	48	SATA1 RX/ PE4 RX	SATA Lane 2 Receive +
SATA Lane 2 Transmit -	PE4-TX#/ SATA1-TX#	49	50	SATA1 RX #/ PE4 RX #	SATA Lane 2 Receive -
Ground	GND	51	52	GND	Ground
PCIe Clock Enable Lane 1 active low	PCKE1#	53	54	PCKE2#	PCIe Lane 2 Clock Enable active low
PCIe Clock Enable Lane 3 -	PCKE3#	55	56	PCKE4#	PCIe Lane 4 Clock Enable -
PCIe Reset active low	PERST#	57	58	PEWAKE#	PCIe Wake active low
SMBus Clock	SMBCLK	59	60	SMBDAT	SMBus Data

KEY

SMBus Alert active low	SMB-Alert#	61	62	1Wire	1-Wire
PCIe Clock Enable Lane 5	PCKE5/OC4#	63	64	PCKE6#/OC3#	PCIe Lane 6 Clock Enable 6 -
PCIe Clock Enable Lane 7	PCKE7/OC2#	65	66	PCKE8#/OC1#	USB Overcurrent active low
Ground	GND	67	68	GND	Ground
PCIe Lane 5 Transmit +	PE5-TX/ USB3-4-TX/ USBC1-TX	69	70	USBC1 RX/ USB3-4 RX/ PE5 RX	PCIe Lane 5 Receive +
PCIe Lane 5 Transmit -	PE5-TX#/ USB3-4-TX#/ USBC1_TX#	71	72	USBC1 RX #/ USB3-4 RX #/ PE5 RX#	PCIe Lane 5 Receive -

USB 2.0 Channel 4 +	USB2-4 (GND)	73	74	USB2-8 (GND)	USB 2.0 Channel 8 Data +
PCIe Clock Lane 5 +	PECLK5/ USBC_SBU1 (GND)	75	76	PECLK6 (GND)	PCIe Lane 6 Clock +
PCIe Clock 5 -	PECLK5#/ USBC-SBU2 (GND)	77	78	PECLK6# (GND)	PCIe Clock Lane 6 -
USB 2.0 Channel 4 -	USB2-4# (GND)	79	80	USB2-8 D# (GND)	USB 2.0 Channel 8 Data -
PCIe Lane 6 Transmit +	PE6-TX/ USB3-3-TX/ USBC2-TX	81	82	USBC2 RX/ USB3-3 RX/ PE6 RX	PCIe Lane 6 Receive +
PCIe Lane 6 Transmit -	PE6-TX#/ USB3-3-TX#/ USBC2-TX#	83	84	USBC2 RX#/ USB3-3 RX#/ PE6 RX#	PCIe Lane 6 Receive -
Ground	GND	85	86	GND	Ground
PCIe Lane 7 Transmit +	PE7-TX/ USB3-2-TX/ SSIC-TX	87	88	SSIC RX/ USB3-2 RX/ PE7 RX	PCIe Lane 7 Receive +
PCIe Lane 7 Transmit -	PE7-TX#/ USB3-2-TX#/ SSIC-TX#	89	90	SSIC RX#/ USB3-2 RX#/ PE7 RX#	PCIe Lane 7 Receive -
USB 2.0 Channel 3 +	USB2-2 (GND)	91	92	USB2-1 (GND)	USB 2.0 Channel 10 +
Ground	PECLK7 (GND)	93	94	PECLK8 (GND)	PCIe Lane 8 Clock +
Ground	PECLK7# (GND)	95	96	PECLK8# (GND)	PCIe Clock Lane 8 -
USB 2.0 Channel 3 -	USB2-2# (GND)	97	98	USB2-1# (GND)	USB 2.0 Channel 10 -
PCIe Lane 8 Transmit +	PE8-TX/ USB3-1-TX	99	100	USB3-1 RX/ PE8 RX	PCIe Lane 8 Receive +
PCIe Lane 8 Transmit -	PE8-TX#/ USB3-1-TX#	101	102	USB3-1 RX#/ PE8 RX#	PCIe Lane 8 Receive -
Ground	GND	103	104	GND	Ground
KEY					
SATA GP1	GPIO1/ SATAGP1	105	106	SATAGP2/ GPIO2	SATA GP 2
SATA GP3	GPIO3/ SATAGP3/ USBC-CC1	107	108	USB-CC2/ SATAGP4/ GPIO4	SATA GP4
TwinCAT LED Red	GPIO5/ TCLEDR	109	110	GPIO6/ TCLEDG	TwinCAT LED Green
TwinCAT LED Blue	GPIO7/ TCLEDB	111	112	GPIO8	(not led out)
SATA LED active low	SATA-LED	113	114	USBPWREN	USB Power Enable
RTC Battery	BATT	115	116	PWRFAIL	SUSV

Power Management Event active low	PME#	117	118	PWRGOOD	Power good
Power button active low	PWRBTN#	119	120	MRST#	Reset button active low
PSON	PSON	121	122	ATXPWRGD	ATX Power good
Ground	GND	123	124	GND	Ground
DisplayPort + / DVI -	DP/DVI#	125	126	DDCC/ DPAUX	DisplayPort Aux +/ DDC Clock
DisplayPort Hot Plug Detect	DPHPD	127	128	DDCD/ DPAUX#	DisplayPort Aux - / DDC Data
Ground	GND	129	130	GND	Ground
DisplayPort Lane 0 +	DPL0	131	132	DPL1	DisplayPort Lane 1 +
DisplayPort Lane 0 -	DPL0#	133	134	DPL1#	DisplayPort Lane 1 -
Ground	GND	135	136	GND	Ground
DisplayPort Lane 2 +	DPL2	137	138	DPL3	DisplayPort 3 +
DisplayPort Lane 2 -	DPL2#	139	140	DPL3#	DisplayPort 3 -

Preliminary

7.3 Internal: FAN

The module has two 4-pin fan connections. This enables fans with a supply voltage of 12 V to be connected directly to the module. A signal is also available for monitoring the fan speed.




Fig. 9: ADL120 FAN

Pin assignment of fan connector:

Pin	Signal	Description
1	GND	Ground
2	12 V	Supply voltage 12 V regulated
3	TACHO	Speed monitoring
4	PWM	Speed control

7.4 Internal: Battery

The board is delivered with a CR2032 battery holder (Renata VBH2032-1) including a 3 V battery.



UL conformity

All technical measures for UL conformity are already integrated on the board.

Accordingly, no additional actions are necessary for the connection of an RTC battery. The battery must be connected directly.




Fig. 10: ADL120 Bat



Synchronism of the RTC

The quartz of the RTC reacts to temperature fluctuations. Therefore, correct synchronism of the RTC is possible only with suitable and sufficient cooling!

8 LEDs

8.1 LED: Power controller

There is an RGB LED on the board with which status messages of the power controller are output by means of colors and flashing intervals.




Fig. 11: ADL120 PWRCTRL-LED

Color	Interval	Meaning
None	Steadily lit	System in error state
White	Steadily lit	Power fail
Cyan	Steadily lit	Reserved
Magenta	Steadily lit	S UPS active (if existent)
Blue	Steadily lit	Reserved
Yellow	Steadily lit	S5 state
Green	Steadily lit	S0 state
Red	Steadily lit	Reset/Start
Green/yellow	Flashing	Bootloader running without error
Red/yellow	Flashing	Bootloader is starting (start sequence is being run through)
Yellow	Flashing (6 s)	S4 state
Yellow	Flashing (3 s)	S3 state
Magenta	Flashing (0.5 s)	S UPS capacitance test (if S UPS exists)
Red/magenta	Flashing	Checksum error during the I2C transmission in the bootloader

A steadily lit red LED can indicate a hardware error.



Adaption of the status codes

It is possible to adapt the status codes (e.g. as TwinCAT LED). To do this, the system colors can be changed with the aid of an SMB command. This change remains in force until the next restart or reset. A change of the default colors is indicated by the additional flashing of the white LED.

8.2 LED: SATA

A further RGB LED indicates the hard disk activity.




Fig. 12: ADL120 SATA-LED

Color	Interval	Meaning
Red	Flashing	Activity (access)

8.3 LED: TwinCAT




Fig. 13: ADL120 TwinCAT LED

Color	Interval	Meaning
Green	Steadily lit	TwinCAT Run Mode
Blue	Steadily lit	TwinCAT Config Mode
Red	Steadily lit	TwinCAT Stop



Adaptation of the status codes

It is possible to adapt the status codes (e.g. as TwinCAT LED). To do this, the system colors can be changed with the aid of an SMB command. This change remains in force until the next restart or reset. A change of the default colors is indicated by the additional flashing of the white LED.

8.4 LED: UPS-OCT

There is an RGB LED on the board with which the transmission quality of the UPS-OCT signals is indicated by means of colors and flashing intervals.




Fig. 14: ADL120 UPS-OCT LED

Color	Interval	Meaning
None	Steadily lit	No UPS-OCT connected
Blue	Flashing	Bootloader active
Yellow	Steadily lit	Moderate signal quality
Green	Steadily lit	Good signal quality
Red	Steadily lit	Poor signal quality

If the LED does not light up, no UPS-OCT is connected.



Adaptation of the status codes

It is possible to adapt the status codes (e.g. as UPS-OCT-LED). To do this, the system colors can be changed with the aid of an SMB command. This change remains in force until the next restart or reset.

9 BIOS

9.1 Main

Board Information		Set the Date. Use Tab to switch between Date elements.
Board	CB6464	
Revision	0	
Bios Version	1.15 Testversion	
Processor Information		
Name	Kabylake DT	
Type	Intel® Core™	
	I7-7700 CPU3.60GHz	
Speed	3600MHz	
ID	0x906E9	
Stepping	B0/S0/M0	
Number of Processors	4Core(s)/4Thread(s)	
Microcode Revision	84	
GT Info	GT2 (0x5912)	
IGFX VBIOS Version	1049	
IGFX GOP Version	N/A	
Memory RC Version	1.7.0.0	
Total Memory	16384 MB	
Memory Frequency	2400 MHz	
System Date	[Mon 01/05/2018]	
System Time	[16:08:25]	

Setup-Entry	Options
Board	None
Revision	None
Bios Version	None
Processor Information	
Name	None
Type	None
Speed	None
ID	None
Stepping	None
Number of Processors	None
Microcode Revision	None
GT Info	None
IGFX VBIOS Version	None
IGFX GOP Version	None
Memory RC Version	None
Total Memory	None
Memory Frequency	None
System Date	Here the systemdate can be changed.
System Time	Here the systemtime can be changed.
PCH Typ	Q170 / H110 (depending on hardware variant: V1 → Q170 V2 → H110)

9.2 Advanced Menu

Power Supply Type SoftOff on Overheat Show postcode on screen ► Platform Misc Configuration ► CPU Configuration ► Intel® Ethernet Connection (2) I219-88:88:88 ► Driver Health ► Trusted Computing ► Hardware Monitor ► PCI Subsystem Settings ► Network Stack Configuration ► Power Controller Options ► CSM Configuration ► NVMe Configuration ► USB Configuration ► SATA And RST Configuration ► AMT Configuration	[ATX] [Disabled] [Disabled] 	Select the Type of the Power Supply: AT/ATX
		←: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit

Setup-Entry	Options
Power-Supply Type	ATX / AT
SoftOff on Overheat	Disabled / Enabled / Enabled (Emulate PwrBtn)
Show postcode on screen	Disabled / Enabled
Platform Misc Configuration	Submenu see: Platform Misc Configuration [► 36]
CPU Configuration	Submenu see: CPU Configuration [► 37]
Intel® Ethernet Connection (2)	Submenu see: Intel Ethernet Connection [► 38]
Driver Health	Submenu see: Driver Health [► 39]
Trusted Computing	Submenu see: Trusted Computing [► 40]
Hardware Monitor	Submenu see: Hardware Monitor [► 40]
PCI Subsystem Settings	Submenu see: PCI Subsystem Settings [► 41]
Network Stack Configuration	Submenu see: Network Stack Configuration [► 42]
Power Controller Options	Submenu see: Power Controller Options [► 43]
CSM Configuration	Submenu see: CSM Configuration [► 44]
NVME Configuration	Submenu see: NVMe Configuration [► 45]
USB Configuration	Submenu see: USB Configuration [► 45]
SATA and RST Configuration	Submenu see: SATA und RST Configuration [► 46]
AMT Configuration	Submenu see: AMT Configuration [► 48]

9.3 Platform Misc Configuration

Platform Misc Configuration		PTID Support will be loaded if enabled.
PTID Support	[Enabled]	
PECI Access Method	[Direct I/O]	
Native PCIE Enable	[Disabled]	
BDAT ACPI Table Support	[Disabled]	
Wake system from S5	[Disabled]	
ACPI Debug	[Disabled]	
Low Power S0 Idle Capability	[Disabled]	
Lpit Recidency Counter	[SLP S0]	
PCI Delay Optimization	[Disabled]	
ZpODD Support	[Disabled]	

←: Select Screen
 ↑↓: Select Item
 Enter: Select
 +/−: Change Opt.
 F1: General Help
 F2: Previous Values
 F3: Optimized Values
 F4: Save&Exit
 ESC: Exit

Bios-Entry	Options
Platform Misc Configuration	
PTID Support	Disabled / Enabled
PECI Access Method	Direct I/O / ACPI
Native PCIE Enable	Disabled / Enabled
BDAT ACPI Table Support	Disabled / Enabled
Wake system from S5	Disabled / Enabled
ACPI Debug	Disabled / Enabled
Low Power S0 Idle Capability	Disabled / Enabled
Lpit Recidency Counter	SLP S0 / C10
PCI Delay Optimization	Disabled / Enabled
ZpODD Support	Disabled / Enabled

9.4 CPU Configuration

CPU Configuration		Enable/Disable Software Guard Extensions (SGX)
Type	Intel® Core™ i7-7700 CPU@3.60GHz	
ID	0x906E9	
Speed	3600 MHz	
L1 Data Cache	32 KB x 4	
L1 Instruction Cache	32 KB x 4	
L2 Cache	256 KB x 4	
L3 Cache	8 MB	
L4 Cache	N/A	
VMX	Supported	
SMX/TXT	Supported	
SW Guard Extensions (SGX)	[Disabled]	
CPU Flex Ratio Override	[Disabled]	
CPU Flex Ratio Settings	36	
Hardware Prefetcher	[Enabled]	
Adjacent Cache Line Prefetch	[Enabled]	
Intel (VMX) Virtualization	[Enabled]	
Technology	[Enabled]	
PECI	[Enabled]	
Active Processor Cores	[All]	
Hyper-Threading	[Disabled]	
AES	[Enabled]	

→: Select Screen
 ↑↓: Select Item
 Enter: Select
 +/-: Change Opt.
 F1: General Help
 F2: Previous Values
 F3: Optimized Values
 F4: Save&Exit
 ESC: Exit

Bios-Entry	Options
CPU Configuration	
Type	None
ID	None
Speed	None
L1 Data Cache	None
L1 Instruction Set	None
L2 Cache	None
L3 Cache	None
L4 Cache	None
VMX	None
SMX/TXT	None
SW Guard Extensions (SGX)	Software Controllers / Enabled / Disabled
CPU Flex Ratio Override	Disabled / Enabled
CPU Flex Ratio Settings	None
Hardware Prefetcher	Disabled / Enabled
Adjacent Cache Line Prefetch	Disabled / Enabled
Intel (VMX) Virtualization Technology	Disabled / Enabled
PECI	Disabled / Enabled
Active Processor Cores	All / 1 / 2 / 3
Hyper-Threading	Disabled / Enabled
AES	Disabled / Enabled
Intel Trusted Execution Technology	Disabled / Enabled
Alias Check Request	Disabled / Enabled
DPR Memory Size (MB)	0..255
Reset AUX Content	Disabled / Enabled
CPU-Power Managemant Control	Submenu see: CPU Power Management Control [▶ 38]

9.5 CPU Power Management Control

CPU - Power Management Control		Enable/Disable Intel® Speed Shift Technology support. Enabling will expose the CPFC v2 interface to allow for hardware controlled P-states.
Intel® SpeedStep™	[Disabled]	---
Intel® Speed Shift Technology	[Disabled]	++: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit

Bios-Entry	Options
CPU-Power Mangement Control	
Intel® SpeedStep	Disabled / Enabled
Intel® Speed Shift Technology	Enabled / Disabled

9.6 Intel Ethernet Connection

PORT CONFIGURATION MENU ► NIC Configuration Blink LEDs	Click to configure the network device port.
PORt CONFIGURATION INFORMATION UEFI Driver: Intel® Gigabit 0.0.16 Adapter PBA: FFFFFFF-0FF Chip Type: Intel PCH SPT PCI Device ID: 15B7 PCI Address: 00:1F:06 Link Status: [Disconnected] MAC Address: 00:00:00:00:07:00	++: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit

Bios-Entry	Options
Port Configuration	
NIC Configuration	Submenu see: NIC Configuration [▶ 39]
Blink LEDs	
Port Configuration Information	
UEFI Driver	None
Adapter PBA	None
Chip Type	None
PCI DEcice ID	None
PCI Address	None
Link Status	None
MAC Address	None

9.7 NIC Configuration

Link Speed Wake On LAN	[Auto Negotiated] [Enabled]	Enable/Disable Software Guard Extensions (SGX) --: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit
---------------------------	--------------------------------	--

Bios-Entry	Options
Link Speed	Auto Negotiated / 10 Mbps Half / 10 Mbps Full / 100 Mbps Half / 100 Mbps Full
Wake On LAN	Disabled / Enabled

9.8 Driver Health

► Intel® Gigabit 0.0.16	Healthy	Provides Health Status for the Drivers/Controllers --: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit
-------------------------	---------	--

Bios-Entry	Options
Intel® Gigabit 0.0.16	Submenu see: Intel Gigabit [► 39]

9.9 Intel Gigabit

Controller b9a29498 Child 0	Healty	Provides Health Status for the Drivers/Controllers --: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit
-----------------------------	--------	--

Bios-Entry	Options
Controller (xxx)	None

9.10 Trusted Computing

Configuration Security Device Support NO Security Device Found	[Disable]	Enables or Disables BIOS support for security device. O.S. will not show Security Device. TCG EFI protocol and INT1A interface will not be available.
		---: Select Screen ↑↓: Select Item Enter: Select +/−: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit

Bios-Entry	Options
Configuration	
Security Device Support	Disable / Enable

9.11 Hardware Monitor

PC Health Status	CPU dig. : +51 °C MB Temp : +44 °C PwrCtrlVCC : +5.20 V	---: Select Screen ↑↓: Select Item Enter: Select +/−: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit
------------------	---	---

Bios-Entry	Options
PC Health Status	
CPU dig.	None
1.00V	None
VCCCORE	None
5V	None
12V	None
Memory VD	None
3.3V	None
Fan 1	None
Fan 2	None
MB Temp	None
Memory Temp	None
PwCtrlTemp	None

9.12 PCI Subsystem Settings

PCI Bus Driver Version	A5.01.12	Value to be programmed into PCI Latency Timer Register.
PCI Devices Common Settings:		
PCI Latency Timer	[32 PCI Bus Clocks]	
PCI-X Latency Timer	[64 PCI Bus Clocks]	
VGA Palette Snoop	[Disabled]	
PERR# Generation	[Disabled]	
SERR# Generation	[Disabled]	
Above 4G Decoding	[Disabled]	
► PCI Hot-Plug Settings		<p>-->: Select Screen ↑↓: Select Item Enter: Select +/ -: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit</p>

Bios-Entry	Options
PCI Bus Driver Version	None
PCI Device Common Settings:	
PCI Latency Timer	32 / 64 / 96 / 128 / 160 / 192 / 224 / 248 / PCI Bus Clocks
PCI-X Latency Timer	32 / 64 / 96 / 128 / 160 / 192 / 224 / 248 / PCI Bus Clocks
VGA Palette Snoop	Disabled / Enabled
PERR# Generation	Disabled / Enabled
SERR# Generation	Disabled / Enabled
Above 4G Decoding	Disabled / Enabled
PCI Hot-Plug Settings	Submenu see: PCI Hot-Plug Settings ► 41]

9.13 PCI Hot-Plug Settings

PCI Hot-Plug Settings		If ENABLED allows BIOS build in Hot-Plug support. Use this feature if OS does not support PCI Express and SHPC hot-plug natively.
BIOS Hot-Plug Support	[Enabled]	
PCI Buses Padding	[1]	
I/O Resources Padding	[4 K]	
MMIO 32 bit Resources Padding	[16 M]	
PFMMIO 32 bit Resources Padding	[16 M]	
		<p>-->: Select Screen ↑↓: Select Item Enter: Select +/ -: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit</p>

Bios-Entry	Options
PCI Hot-Plug Settings	
BIOS Hot-Plug Support	Enabled / Disabled
PCI Buses Padding	Disabled / 1 / 2 / 3 / 4 / 5
I/O Resources Padding	Disabled / 4 K / 8 K / 16 K / 32 K
MMIO 32 bit Resources Padding	Disabled / 1 M / 2 M / 4 M / 8 M / 16 M / 32 M / 64 M / 128 M
PFMMIO 32 bit Resources Padding	Disabled / 1 M / 2 M / 4 M / 8 M / 16 M / 32 M / 64 M / 128 M

9.14 Network Stack Configuration

Network Stack	[Disabled]	Enable/Disable Network Stack
<p>--: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit</p>		

Bios-Entry	Options
Network Stack	Disabled / Enabled
Ipv4 PXE Support	Disabled / Enabled
Ipv4 http Support	Disabled / Enabled
Ipv6 PXE Support	Disabled / Enabled
IPV6 http Support	Disabled / Enabled
IP6 Configuration	Automatic / Manual
PXE boot wait time	0..5
Media detect count	0..50

9.15 Power Controller Options

Bootloader Version	1.01-00	Select Power line for external USB devices, if powered-on
Firmware Version	1.02-00	
Mainboard Serial No	0000000000	
Mainboard Prod. Date (Week.Year)	0.0	
Mainboard BootCount	231	
Mainboard Operation Time	237326min (3955h)	
Voltage (Min/Max)	5.00V/5.10V	
Temperature (Min/Max)	-11'C/92'C	
Ext. USB-Port Voltage	[Off in S3-5]	→: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit
WDT OSBoot Timeout	[Disabled]	
1-second Uninterruptable Power Supply (SUPS)		
SUPS Enable	[Enabled]	
Hold USB	[Enabled]	
Delay	0	
SUPS Firmware Version	0.00	
Current Power Source	Unknown Status:0xED	
Battery Load Level	0%	
Powerfail Counter	0	

Bios-Entry	Options
Bootloader Version	None
Firmware Version	None
Mainboard Serial No	None
Mainboard Prod. Date (Week.Year)	None
Mainboard BootCount	None
Mainboard Operation Time	None
Voltage /Min/Max)	None
Temperature (Min/Max)	None
Ext. USB-Port Voltage	Off in S3-5 / by SCVV
WDT OSBoot Timeout	Disabled / 45 / 60 / ../255 Seconds
1-second Uninteruruptable Power Supply (SUPS)	
SUPS	Disabled / Enabled
Hold USB	Disabled / Enabled
Delay	0..255
SUPS Firmware Version	None
Current Power Source	None
Battery Load Level	None
Powerfail Counter	None

9.16 CSM Configuration

Compatibility Support Module Configuration		Enable/Disable CSM Support.
CSM Support	[Enabled]	
CSM16 Module Version	07.00	
GateA20 Active	[Upon Request]	
Option ROM Messages	[Force BIOS]	
INT19 Trap Response	[Immediate]	
Boot option filter	[UEFI and Legacy]	
Option ROM execution		
Network	[Legacy]	
Storage	[Legacy]	
Video	[Legacy]	
Other PCI devices	[UEFI]	

←: Select Screen
 ↑↓: Select Item
 Enter: Select
 +/−: Change Opt.
 F1: General Help
 F2: Previous Values
 F3: Optimized Values
 F4: Save&Exit
 ESC: Exit

Bios-Entry	Options
Compatibility Support Module Configuration	
CSM Support	Enabled / Disabled
CSM16 Module Version	None
GateA20 Active	Upon Request / Always
Option ROM Messages	Force BIOS / Keep Current
INT19 Trap Response	Immediate / Postponed
Boot option filter	UEFI and Legacy / Legacy only / UEFI only
Option ROM execution	
Network	Do not launch / UEFI / Legacy
Storage	Do not launch / UEFI / Legacy
Video	Do not launch / UEFI / Legacy
Other PCI devices	Do not launch / UEFI / Legacy

9.17 NVMe Configuration

NVMe controller and Drive information	
NO NVMe Device Found	
<pre>-->: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit</pre>	

Bios-Entry	Options
NVMe controller and Drive Information	
[Device list]	None

NOTE

NVMe Raid 0/1 is not supported.

9.18 USB Configuration

USB Configuration		Enable/Disable CSM Support.
USB Module Version	19	
USB Controllers:		
1 XHCI		
USB Devices:		
1 Keyboard		
Legacy USB Support	[Enabled]	
XHCI Hand-off	[Enabled]	
USB Mass Storage Driver Support	[Enabled]	
Port 60/64 Emulation	[Enabled]	
USB hardware delays and time-outs:		
USB transfer time-out	[20 sec]	
Device reset time-out	[20 sec]	
Device power-up delay	[Auto]	
<pre>-->: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit</pre>		

Bios-Entry	Options
USB Configuration	
USB Module Version	None
USB Controllers	None
USB Devices	None
Legacy USB Support	Enabled / Disabled / Auto
XHCI Hand-off	Enabled / Disabled
USB Mass Storage Driver Support	Enabled / Disabled
Port 60/64 Emulation	Disabled / Enabled
USB hardware delays and time-outs	
USB transfer time-out	1 / 5 / 10 / 20 sec
Device reset time-out	10 / 20 / 30 / 40 sec
Device power-up delay	Auto/ Manual

9.19 SATA und RST Configuration

SATA and RST Configuration		Enable/Disable SATA Device.
SATA Controller(s)	[Enabled]	
SATA Mode Selection	[Intel RST Premium]	
SATA Test Mode	[Disabled]	
RAID Device ID	[Client]	
► Software Feature Mask Configuration		
Aggressive LPM Support	[Enabled]	
SATA Controller Speed	[Default]	
Serial ATA Port 0	Empty	--: Select Screen
Software Preserve	Unknown	↑↓: Select Item
Port 0	[Enabled]	Enter: Select
Hot Plug	[Enabled]	+/-: Change Opt.
Configures as eSATA	Hot Plug supported	F1: General Help
Spin Up Device	[Disabled]	F2: Previous Values
Topology	[Unknown]	F3: Optimized Values
SATA Port 0 DevSlp	[Disabled]	F4: Save&Exit
DITO Configuration	[Disabled]	ESC: Exit
Serial ATA Port 1	Empty	
Software Preserve	Unknown	
Port 1	[Enabled]	
Hot Plug	[Enabled]	
Configured as eSATA	Hot Plug supported	
Spin Up Device	[Disabled]	

Bios-Entry	Options
SATA And RST Configuration	
SATA Controller(s)	Enabled / Disabled
SATA Mode Selection	AHCI / Intel RST Premium
SATA Test Mode	Enabled / Disabled
RAID Device ID	Client / Alternate
Software Feature Mask Configuration	Submenu see: Software Feature Mask Configuration [► 47]
Aggressive LPM Support	Disabled / Enabled
SATA Controller Speed	Default / Gen1 / Gen2 / Gen3
Serial ATA Port X	None
Software Preserve	None
Port X	Disabled / Enabled
Hot Plug	Disabled / Enabled
Configured as eSATA	None
Spin Up Device	Disabled / Enabled
Topology	Unknown / ISATA / Direct Connect / FLEX / M2
SATA Port X Dev Slp	Disabled / Enabled
DITO Configuration	Disabled / Enabled

9.20 Software Feature Mask Configuration

Software Feature Mask Configuration		Value to be programmed into PCI Latency Timer Register.
HDD Unlock	[Enabled]	
LED Locate	[Enabled]	
RAID0	[Enabled]	
RAID1	[Enabled]	
RAID10	[Enabled]	
RAID5	[Enabled]	
Intel Rapid Recovery Technology	[Enabled]	
OROM UI and BANNER	[Enabled]	
IRRT Only on eSATA	[Enabled]	
Smart Response Technology	[Enabled]	
OROM UI Normal Delay	[2 secs]	
RST Force Form	[Enabled]	
		←: Select Screen ↑↓: Select Item Enter: Select +/−: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit

Bios-Entry	Options
Software Feature Mask Configuration	
HDD Unlock	Disabled / Enabled
LED Locate	Disabled / Enabled
RAID0	Enabled / Disabled
RAID1	Enabled / Disabled
RAID10	Enabled / Disabled
Raid5	Enabled / Disabled
Intel Rapid Recovery Technology	Enabled / Disabled
OROM UI and BANNER	Enabled / Disabled
IRRT Only on eSATA	Enabled / Disabled
Smart Response Technology	Enabled / Disabled
OROM UI Normal Delay	2 secs / 4 secs / 6 secs / 8 secs
RTS Force Form	Enabled / Disabled

9.21 AMT Configuration

ASF support	[Enabled]	Enable/Disable Alert Standard Format support.
USB Provisioning of AMT	[Disabled]	
<ul style="list-style-type: none"> ▶ CIRA Configuration ▶ ASF Configuration ▶ Secure Erase Configuration ▶ OEM Flags Settings ▶ MEBx Resolution Settings 		

←: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Opt.
F1: General Help
F2: Previous Values
F3: Optimized Values
F4: Save&Exit
ESC: Exit

Bios-Entry	Options
ASF Support	Disabled / Enabled
USB Provisioning of AMT	Disabled / Enabled
CIRA Configuration	Untermenü siehe : CIRA Configuration [▶ 48]
ASF Configuration	Untermenü siehe: ASF Configuration [▶ 49]
Secure Erase Configuration	Untermenü siehe: Secure Erase Configuration [▶ 49]
OEM Flags Settings	Untermenü siehe: OEM Flags Settings [▶ 50]
MEBx Resolution Settings	Untermenü siehe: MEBx Resolution Settings [▶ 51]

9.22 CIRA Configuration

Activate Remote Assistance Process	[Disabled]	Trigger CIRA boot
CIRA Timeout	0	Note: Network Access must be activated first from MEBx Setup.
<p>←: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit</p>		

Bios-Entry	Options
Activate Remote Assistance Process	Disabled / Enabled
CIRA Timeout	0..255

9.23 ASF Configuration

ASF support	[Enabled]	Value to be programmed into PCI Latency Timer Register.
USB Provisioning of AMT ► CIRA Configuration ► ASF Configuration ► Secure Erase Configuration ► OEM Flags Settings ► MEBx Resolution Settings	[Disabled]	←: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit

Bios-Entry	Options
PEt Progress	Disabled / Enabled
WatchDog	Disabled / Enabled
OS Timer	0..65535
BIOS Timer	0..65535

9.24 Secure Erase Configuration

Secure Erase mode Force Secure Erase	[Simulated] [Disabled]	Force Secure Erase on next boot
		←: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit

Bios-Entry	Options
Secure Erase Mode	Simulated / Real
Force Secure Erase	Disabled / Enabled

9.25 OEM Flags Settings

MEB hotkey Pressed	[Disabled]	OEMFlag Bit 1: Enable automatic MEBx hotkey press.
MEBx Selection Screen	[Disabled]	
Hide Unconfigure ME Confirmation Prompt	[Disabled]	
MEBx OEM Debug Menu Enable	[Disabled]	
Unconfigure ME	[Disabled]	

Bios-Entry	Options
MEBx hotkey pressed	Disabled / Enabled
MEBx Selection Screen	Disabled / Enabled
Hide Unconfigure ME Confirmation Prompt	Disabled / Enabled
MEBx OEM Debug Menu Enable	Disabled / Enabled
Unconfigure ME	Disabled / Enabled

9.26 MEBx Resolution Settings

Non-UI Mode Resolution	[Auto]	Resolution for graphics mode.
UI Mode Resolution	[Auto]	
Graphics Mode Resolution	[Auto]	
		→: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit

Bios-Entry	Options
Non-UI Resolution	Auto / 80x25 / 100x31
UI Mode Resolution	Auto / 80x25 / 100 x 31
Graphics Mode Resolution	Auto / 640x 480 / 800x600 / 1024 x 768

9.27 Chipset

► System Agent (SA) Configuration ► PCH-IO Configuration	System Agent (SA) Parameters →: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit
---	---

Setup-Entry	Options
System Agent (SA) Configuration	Submenu see: System Agent (SA) Configuration [▶ 52]
PCH-IO Configuration	Submenu see: PCH-IO Configuration [▶ 55]

9.28 System Agent (SA) Configuration

System Agent (SA) Configuration		Graphics Configuration
SA PCIe Code Version	1.7.0.0	
VT-d	Supported	
▶ Graphics Configuration		←: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized values F4: Save&Exit ESC: Exit
PEG-Port 0:1:0 is assigned to LAN2		
VT-d	[Enabled]	
CHAP Device (B0:D7:F0)	[Disabled]	
Thermal Device (B0:D4:F0)	[Disabled]	
GMM Device (B0:D8:F0)	[Enabled]	
CRID Support	[Disabled]	
Above 4GB MMIO BIOS assignment	[Disabled]	

Bios-Entry	Options
System Agent (SA) Configuration	
SA PCIe Code Version	None
VT-d	None
Graphics Configuration (PEG-Port X assignemnt)	Submenu see: Graphics Configuration [▶ 53]
VT-d	Disabled / Enabled
Chap Device	Disabled / Enabled
Thermal Device	Disabled / Enabled
GMM Device	Disabled / Enabled
CRID Support	Disabled / Enabled

9.29 Graphics Configuration

Graphics Configuration		Click to configure the network device port.
Graphics Turbo IMON Current	31	
Skip Scaning of External Gfx Card	[Disabled]	
Primary Display	[Auto]	
Select PCIE Card	[Auto]	
► External Gfx Card Primary Display Configuration		
Internal Graphics	[Auto]	
GTT Size	[8MB]	
Aperture Size	[256MB]	
DVMT Pre-allocated	[32M]	
DVMT Total Gfx Mem	[256M]	
Gfx Low Power Mode	[Enabled]	
VDD Enable	[Enabled]	
HDCP Support	[Enabled]	
Algorithm	[One-time]	
PM Support	[Enabled]	
Set Power Clamp	[Disabled]	
PAVP Enable	[Enabled]	
Cdynmax Clamping Enable	[Enabled]	
Cd Clock Frequency	[675 Mhz]	
IUER Button Enable	[Disabled]	
► LCD Control		

Bios-Entry	Options
Graphics Configuration	
Skip Scanning of External Gfx Card	Disabled / Enabled
Primary Display	Auto / IGFX / PEG / PCI / SG
Select PCIE Card	Auto / Elk Creek 4 / PEG Eval
External Gfx Card Primary Display Configuration	Submenu see: External Gfx Card Primary Display Configuration [▶ 54]
Internal Graphics	Auto / Disabled / Enabled
GTT Size	2 MB / 4 MB / 8 MB
Aperture Size	128MB / 256MB / 512MB / 1024MB / 2048MB
DVMT Pre-allocated	32M / 64M / 4M / 8M / 12M / 16M / 20M / 24M / 28M / 32M / 36M / 40M / .. / 60M
DVMT Total Gfx Mem	256M / 128M / MAX
Gfx Low Power Mode	Enabled / Disabled
VDD Enable	Enabled / Disabled
HDCP Support	Enabled / Disabled
Algorithm	One-time / Periodic
PM Support	Enabled / Disabled
Set Power Clamp	Disabled / Enabled
PAVP Enable	Enabled / Disabled
Cdynmax Clamping Enable	Enabled / Disabled
Cd Clock Frequency	337.5 Mhz / 450 Mhz / 540 Mhz / 675 Mhz
IUER Button Enable	Disabled / Enabled
LCD Control	Submenu see: LCD Control [▶ 54]

9.30 External Gfx Card Primary Display Configuration

External Gfx Card Primary Display Configuration		Click to configure the network device port.
Primary PEG	[Auto]	→: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit
Primary PCIE	[Auto]	

Bios-Entry	Options
External Gfx Card Primary Display Configuration	
Primary PEG	Auto / PEG11 /PEG12
Primary PCIE	Auto / PCIE1 / PCIE2 / PCIE3 / ... / PCIE19

9.31 LCD Control

LCD Control		Select the Video Device which will be activated during POST. This has no effect if external graphics present. Secondary boot display selection will appear based on your selection. VGA modes will be supported only on primary display.
Primary IGFX Boot Display	[VBIOS Default]	→: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit
LCD Panel Type	[VBIOS Default]	
Panel Scaling	[Auto]	
Backlight Control	[PWM Normal]	
Active LFP	[eDP Port-A]	
Panel Color Depth	[18 Bit]	
Backlight Brightness	255	

Bios-Entry	Options
LCD Control	
Primary IGFX	VBIOS Default / EFP (/ EFP2 / EFP3)
LCD Panel Type	VBIOS Default / 640x480 LVDS / 800x600 LVDS / 1024x768 LVDS / 1280x1024 LVDS / 1400x1050 LVDS1 / 1400x1050 LVDS2 / 1600x1200 LVDS / 1280x768 LVDS / 1680x1050 LVDS / 1920x1200 LVDS / 1600x900 LVDS / 1280x800 LVDS / 1280x600 LVDS / 2048x1536 LVDS / 1366x768 LVDS
Panel Scaling	Auto / Off / Force Scaling
Backlight Control	PWM Inverted / PWM Normal
Active LFP	Noe DP / eDP Port-A
Panel Color Depth	18 Bit / 24 Bit
Backlight Brightness	0..255

9.32 PCH-IO Configuration

PCI Express Configuration		PCI Express Clock Gating Enable/Disable for each root port.
PCI Express Clock Gating	[Enabled]	
Legacy IO Low Latency	[Disabled]	
Peer Memory Write Enable	[Disabled]	
Compliance Test Mode	[Disabled]	
PCIe-USB Glitch W/A	[Disabled]	
► PCI Express Gen3 Eq Lanes		+--: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit
► PCI Express Root Port 1		
PCIE Port 5 is assigned to LAN3		
PCIE Port 6 is assigned to LAN4		
► PCI Express Root Port 9		
► PCI Express Root Port 10		
► PCI Express Root Port 11		
PCIE Port 12 is assigned to LAN		
PCIE Port 13 is ass. to M.2-Slot0		
PCIE Port 14 is ass. to M.2-Slot1		

Bios-Entry	Options
PCH-IO Configuration	
PCI Express Configuration	Submenu see: PCI Express Configuration [▶ 56]
USB Configuration	Submenu see: USB Configuration [▶ 58]
HD Audio Configuration	Submenu see: HD Audio Configuration [▶ 59]
PCH LAN Controller	Enabled / Disabled bei V1, always Enabled bei V2
Wake on LAN	Enabled / Disabled
Second LAN Controller	Enabled / Disabled
Third LAN Controller	Enabled / Disabled
Forth LAN Controller	Enabled / Disabled
M.2-Slot X	None
CLKRUN#logic	Enabled / Disabled
State After G3	S0 State / S5 State
Compatible Revision ID	Enabled / Disabled

9.33 PCI Express Configuration

PCI Express Configuration		PCI Express Clock Gating Enable/Disable for each root port.
PCI Express Clock Gating	[Enabled]	
Legacy IO Low Latency	[Disabled]	
Peer Memory Write Enable	[Disabled]	
Compliance Test Mode	[Disabled]	
PCIe-USB Glitch W/A	[Disabled]	
► PCI Express Gen3 Eq Lanes		
► PCI Express Root Port 1		←: Select Screen
PCIE Port 5 is assigned to LAN3		↑↓: Select Item
PCIE Port 6 is assigned to LAN4		Enter: Select
► PCI Express Root Port 9		+/-: Change Opt.
► PCI Express Root Port 10		F1: General Help
► PCI Express Root Port 11		F2: Previous Values
PCIE Port 12 is assigned to LAN		F3:
PCIE Port 13 is ass. to M.2-Slot0		Optimized Values
PCIE Port 14 is ass. to M.2-Slot1		F4: Save&Exit
		ESC: Exit

Bios-Entry	Options
PCI Express Configuration	
PCI Express Clock Gating	Disabled / Enabled
Lagacy IO Low Latency	Disabled / Enabled
Peer Memory Write Enable	Disabled / Enabled
Compliance Test Mode	Disabled / Enabled
PCIe-USB Glitch W/A	Disabled / Enabled
PCI Express Gen3 Eq Lanes	Submenu see: PCI Express Gen3 Eq Lanes ► 56
PCI Express Root Port X	Submenu see: PCI Express Root Port X ► 57
[PCIE Port assignments]	None

9.34 PCI Express Gen3 Eq Lanes

PCIE1 Cm	6	
PCIE1 Cp	2	
PCIE2 Cm	6	
PCIE2 Cp	2	
PCIE3 Cm	6	
PCIE3 Cp	2	
PCIE4 Cm	6	
PCIE4 Cp	2	
PCIE5 Cm	6	
PCIE5 Cp	2	
PCIE6 Cm	6	
PCIE6 Cp	2	
PCIE7 Cm	6	
PCIE7 Cp	2	←: Select Screen
PCIE8 Cp	6	↑↓: Select Item
PCIE8 Cm	2	Enter: Select
PCIE9 Cp	6	+/-: Change Opt.
PCIE9 Cm	2	F1: General Help
PCIE10 Cp	6	F2: Previous Values
PCIE10 Cm	2	F3:
PCIE11 Cp	6	Optimized Values
PCIE11 Cm	2	F4: Save&Exit
PCIE12 Cp	6	ESC: Exit
PCIE12 Cm	2	
PCIE13 Cp	6	

Bios-Entry	Options
PCIEX Cm	0..63
PCIEX Cp	0..63

9.35 PCI Express Root Port X

PCI Express Root Port 1 Topology	[Enabled] [Unknown]	Control the PCI Express Root Port.
ASPM	[Disabled]	
L1 Substates	[Disabled]	
Gen3 Eq Phase3 Method	[Software Search]	
UPTP	5	
DPTP	7	
ACS	[Enabled]	
URR	[Disabled]	
FER	[Disabled]	
NFER	[Disabled]	
CER	[Disabled]	
CTO	[Disabled]	
SEFE	[Disabled]	
SENFE	[Disabled]	
SECE	[Disabled]	
PME SCI	[Enabled]	
Hot Plug	[Disabled]	
Advanced Error Reporting	[Enabled]	
PCIe Speed	[Auto]	
Transmitter Half Swing	[Disabled]	
Detect Timeout	0	
Extra Bus Reserved	0	
Reserved Memory	10	
Reserved I/O	4	

←: Select Screen
 ↑↓: Select Item
 Enter: Select
 +/-: Change Opt.
 F1: General Help
 F2: Previous Values
 F3: Optimized Values
 F4: Save&Exit
 ESC: Exit

Bios-Entry	Options
PCI Express Root Port 1	Disabled / Enabled
Topolgy	Unknown / x1 / x4 / Sata Express / M2
ASPM	L0sL1 / L1 L0s / Disabled / Auto
L1 Substates	Disabled / L1.1 & L1.2 / L1.1 / L1.2
Gen3 Eq Phase3 Method	Hardware / Static Coeff. / Software Search
UDTP	0..10
DPTP	0..10
ACS	Disabled / Enabled
URR	Disabled / Enabled
FER	Disabled / Enabled
NFER	Disabled / Enabled
CER	Disabled / Enabled
CTO	Disabled / Enabled
SEFE	Disabled / Enabled
SENFE	Disabled / Enabled
SECE	Disabled / Enabled
PME SCI	Disabled / Enabled
Hot Plug	Disabled / Enabled
Advanced Error Reporting	Disabled / Enabled
PCIe Speed	Auto / Gen1 / Gen2 / Gen3
Transmitter Half Swing	Disabled / Enabled
Detect Timeout	0..65535
Extra Bus Reserved	0..7
Reserved I/O	4K / 8K / 12K / 16K / 20K
PCH PCIe LTR Configuration	
PCH PCIE1 LTR	Disabled / Enabled
Snoop Latency Override	Disabled / Manual / Auto
Snoop Latency Value	0..1023
Snoop Latency Multipler	1 ns / 32 ns / 1024 ns / 32768 ns / 1048576 ns / 33554432 ns
Non Snoop Latency Override	Disabled / Manual / Auto

9.36 Extra Options

Detect Non-Compliance Device [Disabled]	Detect Non-Compliance PCI Express Device. If enabled, it will take more time at POST time.
Prefetchable Memory 10 Reserved Memory Alignment 1 Prefetchable Memory Alignment 1	<pre>-->: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit</pre>

Bios-Entry	Options
Detect Non-Compliance Device	Disabled / Enabled
Prefetchable Memory	1..20
Reserved Memory Alignment	1..31
Prefetchable Memmory Alignment	1..31

9.37 USB Configuration

USB Configuration	XHCI Disable Compliance Mode [FALSE] USB Port Disable Override [Disabled]	Options to disable Compliance Mode. Default is FALSE to not disable Compliance Mode. Set TRUE to disable Compliance Mode.
		<pre>-->: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit</pre>

Bios-Entry	Options
USB Configuration	
XHCI Diable Compliance Mode	False / True
USB Port Disable Override	Disabled / Select Per-Pin
USB SS Physical Connector #X	Disabled / Enabled

9.38 HD Audio Configuration

HD Audio Subsystem Configuration Settings		Control Detection of the HD-Audio device. Disabled = HAD will be unconditionally disabled Enabled = HAD will be unconditionally enabled Auto = HAD will be enabled if present, disabled otherwise.
HD Audio	[Disabled]	→: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit

Bios-Entry	Options
HD Audio System Configuration Settings	
HD Audio	Disabled / Enabled / Auto

9.39 Security

Password Description		Set Administrator Password
Minimum length	3	→: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit
Maximum length	20	
Administrator Password		
User Mode available	[Enabled]	
► Secure Boot		

Setup-Entry	Options
Password Description	
Minimum length	None
Maximum length	None
Administrator Password	Here an administrator password can be set.
User Mode	Enabled / Disabled
Secure Boot	Submenu see: Secure Boot [► 60]

9.40 Secure Boot

System Mode	User	Secure Boot mode selector: Standard/Custom.
Secure Boot	Not Active	In Custom mode Secure Boot Variables can be configured without authentication
Vendor Keys	Active	
Attempt Secure Boot	[Enabled]	
Secure Boot Mode	[Standard]	
► Key Management		<pre>--: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit</pre>

Bios-Entry	Options
System Mode	None
Secure Boot	None
Vendor Keys	None
Attempt Secure Boot	Disabled / Enabled
Secure Boot Mode	Standard / Custom
Key Management	Submenu see: Key Management [▶ 60]

9.41 Key Management

Provision Factory Defaults	[Disabled]	Allow to provision factory default Secure Boot keys when System is in Setup Mode
► Reset to Setup Mode		
► Enroll Efi Image		
► Save all Secure Boot variables		
Secure Boot variable	Size Keys# Key Score	
► Platform Key(PK)	862 1 Test(AMI)	
► Key Exchange Keys	1560 1 Default	
► Authorized Signatures	3143 2 Default	
► Forbidden Signatures	3724 77 Default	
► Authorized TimeStamps	0 0 No Key	
► OsRecovery Signatures	0 0 No Key	

Bios-Entry	Options
Provision Factory Defaults	Disabled / Enabled
Reset to Setup Mode	Press entry key
Enroll Efi Image	Press entry key
Save all Secure Boot variables	Press entry key
PlatformKey(PK)	Press entry key
Key Exchange Keys	Press entry key
Authorized Signatures	Press entry key
Forbidden Signatures	Press entry key
Authorized TimeStamps	Press entry key
OsRecovery Signatures	Press entry key

9.42 Boot

Boot Configuration		Sets the system boot order
Setup Prompt Timeout	5	
Bootup NumLock State	[On]	
F7 Boot Menu	[Enabled]	
Full Screen Logo	[Enabled]	
Fast Boot	[Disabled]	
New Boot Option Policy	[Default]	
StartUpDelay for UEFI shell	5	
Boot mode select	[DUAL]	
FIXED BOOT ORDER Priorities		
Boot Option #1	[UEFI Hard Disk]	→: Select Screen
Boot Option #2	[Cfast/SSD]	↑: Select Item
Boot Option #3	[Hard Disk]	Enter: Select
Boot Option #4	[UEFI CD/DVD]	+/-: Change Opt.
Boot Option #5	[UEFI USB Hard Disk]	F1: General Help
Boot Option #6	[UEFI USB CD/DVD]	F2: Previous Values
Boot Option #7	[UEFI USB Stick]	F3:
Boot Option #8	[UEFI USB Floppy]	Optimized Values
Boot Option #9	[USB Hard Disk]	F4: Save&Exit
Boot Option #10	[USB CD/DVD]	ESC: Exit
Boot Option #11	[CD/DVD]	
Boot Option #12	[Service Stick]	

Bios-Entry	Options
Boot Configuration	
Setup Prompt Timeout	0..65535
Bootup NumLok State	On / Off
F7 Boot Menu	Disabled / Enabled
Full Screen Logo	Disabled / Enabled
Fast Boot	Disabled / Enabled
New Boot Option Policy	Default / Place First / Place Last
StartUpDElay for UEFI shell	0..255
Boot mode select	Legacy / UEFI / Dual
Fixed Boot Order Priorities	
Boot Option #1-19	Here the range of boot media to be used can be set.
Advanced Fixed Boot Order Parameters	Submenu see: Fixed Boot Order Parameters [▶ 62]

9.43 Fixed Boot Order Parameters

Max. Cfast/SSD capacity (GB)	200	Capacity limit for boot group Cfast/SSD in GB
Max. USB Stick capacity (GB)	64	

←: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit		

Bios-Entry	Options
Max. CFast/SSD capacity	1..16384
Max. USB Stick capacity (GB)	1..16384

9.44 Save & Exit

Save Changes and Reset	Reset the system after saving the changes.
Discard Changes and Reset	
Restore Optimized Defaults	
Boot Override	
IBA CL Slot 00FE v0110	
Launch EFI Shell from filesystem device	

←: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Values F4: Save&Exit ESC: Exit	

Bios-Entry	Options
Save Changes and Reset	
Discard Changes and Reset	Press entry key
Restore Optimized Defaults	Press entry key
Boot Override	
IBA CL slot 00FE v0110	Press entry key
Launch EFI Shell from filesystem device	Press entry key

10 Mechanical drawings



Dimensional notation

All dimensions are in mil (1 mil = 0.0254 mm). Data in square brackets are in mm.

10.1 PCB: Holes




Fig. 15: MZ MH ADL120

10.2 PCB: Pin 1 distances




Fig. 16: MZ Pin1 ADL120

10.3 PCB: Dimensions




Fig. 17: MZ ADL120

11 Technical data

11.1 Electrical data

Power supply	
Board	24 V (+/- 5%)
RTC	>= 3 µm
Power consumption	
RTC	<= 10 µW

11.2 Environmental conditions

Temperature range	
Operating	0 °C up to +60 °C (more extended temperature range on request)
Storage	-25 °C up to +85 °C
Dispatch	-25 °C up to +85 °C, for wrapped boards
Temperature changes	
Operating	0.5 °C per minute, 7.5 °C in 30 minutes
Storage	1.0 °C per minute
Dispatch	1.0 °C per minute, for wrapped boards
Relative air humidity	
Operating	5% up to 85% (non-condensing)
Storage	5% up to 95% (non-condensing)
Dispatch	5% up to 100% (non-condensing), for wrapped boards
Impact	
Operating	150 m/s², 6 ms
Storage	400 m/s², 6 ms
Dispatch	400 m/s², 6 ms, for wrapped boards
Vibration	
Operating	10 up to 58 Hz, 0.075 mm amplitude
Storage	5 up to 9 Hz, 3.5 mm amplitude 9 up to 500 Hz, 10 m/s²
Dispatch	5 up to 9 Hz, 3.5 mm amplitude 9 up to 500 Hz, 10 m/s², for wrapped boards



Note on impact and vibration resistance

The specifications for impact and vibration resistance refer only to the motherboard itself without heat sink, memory module, cabling, etc.

11.3 Technical specifications

The board is specified for an ambient temperature range of 0 °C to +60 °C (extended temperature range on enquiry). In addition, care must be taken that the temperature of the processor die does not exceed 100 °C. A suitable cooling concept must be implemented for this that is oriented to the maximum power consumption of the processor/chipset. Please note: also that any existing controllers are included in the cooling concept. The power consumption of these modules may be of the same order of magnitude as the power consumption of the processor.

The board is prepared with suitable holes for the use of modern cooling solutions. We have a series of compatible cooling components in our range. Your distributor will be glad to advise you on choosing suitable solutions.

NOTE

Prevent the maximum die temperature being exceeded!

It is the end customer's responsibility to ensure that the die temperature of the processor does not exceed 100 °C! Continuous overheating can destroy the board!

If the temperature exceeds 100 °C, the ambient temperature needs to be reduced. Ensure sufficient air circulation if necessary.

12 Support

12.1 Technical Support

Technical support for this product can be obtained in the following ways:

- By contacting our support staff at +1 858-490-0597 or +49 (0) 271 250 810 0
- By contacting our staff via e-mail at support@adl-usa.com or support@adl-europe.com
- Via our website at www.adl-usa.com/support or www.adl-europe.com/support

Preliminary

13 Appendix I: Post Codes

During the boot phase, the BIOS generates a series of status messages (so-called "POST Codes"), which can be output with the help of a suitable reading device (POST Code card). The meanings of the POST Codes are explained in the document "Aptio™ 5.x Status Codes" from American Megatrends®, which is available from the website <http://www.ami.com>. In addition, the following OEM POST Codes are output:

Code	Description
87h	BIOS-API started
88h	PCA9535 started
89h	PWRCTRL firmware started

Preliminary

14 Appendix II: Resources

14.1 Interrupt

The resources used are independent of the setup setting. The listed interrupts and their use are given by the AT compatibility. If interrupts have to be exclusively available on the ISA side, they must be reserved through the BIOS setup. Exclusivity is neither given nor possible on the PCI side.

Address	Function
IRQ0	Timer
IRQ1	
IRQ2	
IRQ3	
IRQ4	
IRQ5	
IRQ6	
IRQ7	
IRQ8	RTC
IRQ9	
IRQ10	
IRQ11	
IRQ12	
IRQ13	FPU
IRQ14	
IRQ15	

14.2 PCI Devices

The PCI devices listed here all exist on the board, including those that are detected and configured by the BIOS. Due to the BIOS setup settings it may be the case that various PCI devices or functions of devices are not activated. If devices are deactivated, the bus numbers of other devices may change as a result.

INT	REQ	Bus	Dev.	Fct.	Controller / Slot
-	-	0	0	0	Host Bridge ID 191F
	-	0	1	0	PCI Bridge (0-1) x1(x16) ID1901
A	-	0	2	0	VGA Controller ID1912
A	-	0	08	0	System Peripheral ID1911
A	-	0	20	0	XHCI Controller IDA12F
A	-	0	20	2	Other DPIO Module ID1311
A	-	0	22	0	Serial Other IDA13A
A	-	0	23	0	SATA (AHCI 1.0) IDA102
A	-	0	28	0	PCI Bridge (0-2) x1 (x1) IDA114
B	-	0	28	0	PCI Bridge (0-3) x1 (x1) IDA115
	-	0	31	0	ISA Bridge IDA143
	-	0	31	2	Memory Controller IDA121
	-	0	31	4	SMBus Controller IDA123
B	-	0	31	6	Ethernet Controller ID15B7
A	-	1	00	0	Ethernet Controller x1 (x1) ID1531
		2	00	0	Ethernet Controller x1 (x1) ID1531
		3	00	0	Ethernet Controller x1 (x1) ID1531

14.3 SMB-Devices

The following table lists the reserved SM-Bus device addresses in 8-bit notation.

NOTE

These address ranges may not be used by external devices even if the component assigned in the table doesn't exist on the motherboard.

Address	Function
34-35	API access to power supply unit
36-39	Reserved
5C-5D	NCT7491
60-6F	Reserved for DDR4
70-73	POST Code output
88-89	Slave address defined by BIOS
92-93	I210 default
A0-A7	Reserved for DDR4
B0-B3	Power controller (access via BIOS-API)
B8-BB	Power controller (access via BIOS-API)